


Instruction Manual

BODY COMPOSITION ANALYZER DC-360



REMOTE DISPLAY VERSION

COLUMN MOUNTED VERSION



Please read this Instruction Manual carefully and keep it for future reference.

Contents

Before Use

For Your Safety4	ŀ
Part Names & Connection Procedure8	}
Setting the Printer Paper /	
Setting an SD Card/Positioning the Scale10)
Power Supply12)
Settings13	}

How to Use

Taking a Measurement	15
Body Composition Mode	15
Measurement Results	17
Scale Mode	19
Various Criteria	20
What is body fat percentage?	20
What is total body water percentage?	21
What is visceral fat rating?	21
What is basal metabolic rate (BMR)?	22
What is metabolic age?	22
What is muscle mass?	23
What is physique rating?	23
What is bone mass?	24
Output and Storage of Measurement Results	25

If Necessary


Troubleshooting	31
Technical Notes	32
The Regression Formula for	
Basal Metabolic Rate (BMR)	36
Specifications	38

For Your Safety

This section explains precautionary measures to be taken to avoid injury to the users of this device and others, and to prevent damage to property. Please familiarize yourself with this information to ensure safe operation of this equipment.

A Warning	Failure to follow instructions highlighted with this mark could result in death or severe injury.
A Caution	Failure to follow instructions highlighted with this mark could result in injury or damage to property.
\bigcirc	This mark indicates actions that are prohibited.
	This mark indicates instructions that must always be followed.

A Warning



	Keep away from water.		
	Avoid using on subjects with metal allergies.		
\frown	Allergic reactions may be caused by the stainless steel used in the electrodes of this device.		
	Do not jump on the equipment.		
	Do not lean on the equipment.		
V	Do not use this equipment near other products that emit electromagnetic waves.		
rohibited	Do not insert fingers into gaps or holes.		
	Do not apply force to the display.		
	The screen panel may break and cause injury.		
	Assist persons with disabilities or children under 15 years old.		
	A person who is familiar with the device should assist persons with disabilities or children unde		
	15 years old who may not be able to take measurements alone.		
	15 years old who may not be able to take measurements alone. Clean the scale platform with appropriate disinfectant after each use.		
	Clean the scale platform with appropriate disinfectant after each use.		
	Clean the scale platform with appropriate disinfectant after each use. Stand clear of the subject during measurement to ensure accuracy. Continually monitor both the subject and the equipment for anomalies.		
	Clean the scale platform with appropriate disinfectant after each use. Stand clear of the subject during measurement to ensure accuracy. Continually monitor both the subject and the equipment for anomalies. If an anomaly in the subject or equipment is discovered, take appropriate action, such as stopping		
0	Clean the scale platform with appropriate disinfectant after each use. Stand clear of the subject during measurement to ensure accuracy. Continually monitor both the subject and the equipment for anomalies. If an anomaly in the subject or equipment is discovered, take appropriate action, such as stopping the equipment, while ensuring the safety of the subject.		
D Iways	Clean the scale platform with appropriate disinfectant after each use. Stand clear of the subject during measurement to ensure accuracy. Continually monitor both the subject and the equipment for anomalies. If an anomaly in the subject or equipment is discovered, take appropriate action, such as stopping the equipment, while ensuring the safety of the subject. Use the included AC adapter.		
D Iways	Clean the scale platform with appropriate disinfectant after each use. Stand clear of the subject during measurement to ensure accuracy. Continually monitor both the subject and the equipment for anomalies. If an anomaly in the subject or equipment is discovered, take appropriate action, such as stopping the equipment, while ensuring the safety of the subject. Use the included AC adapter. Do not lean against the equipment.		
D Iways	Clean the scale platform with appropriate disinfectant after each use. Stand clear of the subject during measurement to ensure accuracy. Continually monitor both the subject and the equipment for anomalies. If an anomaly in the subject or equipment is discovered,take appropriate action, such as stopping the equipment, while ensuring the safety of the subject. Use the included AC adapter. Do not lean against the equipment. Unplug the AC cord from the equipment when moving it.		

Avoid measuring after strenuous exercise.

This may cause inaccurate measurements. Please take measurements after sufficient rest.

Avoid measuring after excessive food or fluid intake or when dehydrated.

For Accurate Measurements

This may cause inaccurate measurements. For greater accuracy, avoid using directly after waking up. Use at the same time on each occasion, at least three hours after a meal.

Ensure inner thighs are not touching each other during measurement. If necessary, place a dry towel between thighs.

Do not take measurements while using transmitting devices, such as mobile phones, which may affect readings.

Use the equipment under the same conditions and in the same position as much as possible for accurate tracking of changes.

Readings are affected by the level of hydration and position of the body. Please use at the same time of day each time, under the same conditions and in the same body position.

Avoid measuring in multiple locations with greatly differing temperatures.

This may cause inaccurate measurements. Allow the equipment to stand for at least 2 hours before using if it is moved to a new location with a temperature difference of 20°C or more.

Make sure the soles of feet are free of excess dirt, as this may block the mild electric current.

Bare feet should be placed correctly on the electrode platform. Place arms straight down during measurement.

Use in a stable location.

Errors in measurements may occur if the device is used in an unstable location.

Do not wipe the equipment with corrosive chemicals (gasoline, cleaner, etc.). Please use a neutral detergent to clean the equipment.

en









Before Use

en


Scheduled Maintenance

TANITA recommends that each facility conduct periodic checks of each unit.


- 1. Check the following at least daily:
 - The unit is on a stable and level surface on a firm flooring, not on a thick carpet
 - Date and time settings
- 2. Visually inspect the following at least weekly:
 - The display for any damage or contamination
 - All cables, cords, and connector ends for damage or contamination
 - All safety-related labeling for legibility
 - All accessories (electrodes, etc.) for wear or damage
- 3. Visually inspect the following at least monthly:
 - Mounting screws on stand

Update settings, replace items, or call for service as necessary according to the results of the visual inspections. Do not use the unit if you see any signs of damage. Equipment that has been damaged must be checked for proper operation by qualified personnel before using again.

Part Names & Connection Procedure



Display and Keys



Meanings of the LED Indicators and Keys

(0/Ò)	Turn ON / OFF the power	
	Feeds the printer paper	
Setting	Set various functions	
→0 ←	Reset zero point	
(Clothes Weight) 0.0-10.0kg	Set preset value (Clothes weight)	
	Select measurement mode	
	Select measurement display	

FAT	Display Body Fat (percentage and mass) *Not measured value but calculated value			
Muscle	Display Body Muscle (percentage and mass) *Not measured value but calculated value			
Water	Display Body Water (percentage and mass) *Not measured value but calculated value			
Visceral	Display Visceral Fat Rating		BMR	Display Basal Metabolic Rate
O 🛉 STEP ON	STEP ON Indicate to step on			
○ ()Standard	Select the body type from "Standard mode" or "Athletic mode"			
O 🋉 Male	Female	Select the gender from "Male" or "Female"		
🔿 🙀 Age	5 to 99	Enter the age between "5 to 99 years"		
🖸 👖 Height	90.0 to 249.9cm	Enter the height between "90.0cm to 249.9cm"		
Enter	Confirms the entered numerical value.			


en

Setting the Printer Paper / Setting an SD Card/Positioning the Scale

en

Setting the Printer Paper

- (1) Turn the power OFF and push the handle on the left hand side of the controller.
- (2) Open the printer cover.
- (3) Set the printer paper in place. Peel off the adhesive and pull out approximately 10cm of paper from the printer paper.
- (4) Replace the printer cover to its original place.







Press (00) to turn on the device.

After all the indicators are displayed, Dbus is displayed.

If the device is turned on with the printer cover open, [DPEn] is displayed.



Press (b). The printer paper is cut automatically, and the settings are completed.



Paper is not automatically cut when 'Auto Cut' is set to 'Off'.

Note

Cutting automatically setting \rightarrow See P.13 setting4

Setting an SD Card

When the power is turned OFF, insert an SD card into the slot with the logo side facing upwards.


Make sure the card is facing in the correct direction when inserting it.



2

Press oo to turn on the device.

When the device detects the SD card, the mark on the right appears in the upper left corner of the screen.




Be sure to insert and remove the SD card when the device power is off to avoid damaging the SD card.

Note Compatible with SD and SDHC memory cards Not compatible with SDXC memory cards

Positioning the Scale

To obtain the highest level of accuracy, please make sure that all four (4) feet are touching the floor evenly.

For further accuracy and security, position the two adjustable supporting feet until they just make contact with the floor (do not overextend).



Power Supply

Before Use


Turning the Main Power ON/OFF

Turning the main power ON. Press the ∞ key to turn on the power. The initial screen is displayed. јрт ≝ Во Со кај

Turning the main power OFF. Press the \odot key to turn on the poweroff.

Emergency Shut Down

Keep the area around the plug socket clear during operation of the equipment in case of an emergency.



Settings

SEŁ

Note

• The (setting) key cannot be used when the scale is measuring weight or results are displayed while standing on the platform after measurment.

Select the setting item from the list below. Enter numerical values and Press the *CEnter* key.

Setting item List \bigcirc Enter) \rightarrow Save changes and return

Press the setting key to change the mode.

The setting screen is displayed.

 $(CE) \rightarrow Correct input number or cancel$

0	Check the software version	11	Automatic determination time of input information
1	Date and time * Date and time → *See Note below		(0-9 second(s)) (Default: 0) * 0: Disables this function
2	Number to be printed automatically (0-3 sheet(s)) (Default: 1)	18	Target body fat ratio input (0: off 1: on) (Default: 0)
4	Cutting automatically (0: off 1: on) (Default: 1)	19 Printout language (1: English, 2: French, 3: German, 4: Spanish, 5: Italy, 6: Turkey) (Default: 1)	
5	Beep sound (0: off 1: on) (Default: 1)	20	Printout contents (1: full 2: short) (Default: 1)
7	ID number (Automatic count up) (0: off 1: on) (Default: 0)	21	Timeout function of result display (0: disable 1: enable) (Default: 0)
8	 8 Measurement flow (0: off Two step flow / Measure body weight first 1: on One step flow / Enter personal info first) (Default: 0) * Measurement flow → See P.15 		BMR kJ unit displayON/OFF (0: off 1: on) (Default: 1)
			Change the standard BMI range (0: 18.5–25 1: 18.5–24 2: 18.5–23) (Default: 0)
9	Body type selection (Athletic mode) (0: off 1: on) (Default: 1) * Athletic mode → See P.15&P.30	45–67	Printing item settings (0: off 1: on) \rightarrow See P.26
10	Height input unit (0: off 0.1cm increments 1: on 1cm increments) (Default: 0)	80	SD Card mode \rightarrow See P.29

Note

Enter the year, month, day, hour and minute. The date format is "yyyy mm dd hh:mm" (Date input range: 2015 01 01 00:00 to 2099 12 31 23:59)

Example 3:45 pm, 10th April, 2015 "2015" "04 10" "15:45"

To enter a number with 1 digit (0 to 9), press "0" first.




Settings (continued)

Select the Measurement Mode

Select the measurement mode by pressing the (•) key.


The measurement mode is switched in the following order when the

key is pressed:



The "**I**" mark is displayed when the scale mode is selected.

Body Composition Mode



Taking a Measurement

Body Composition Mode

(Two step flow Measure body weight first) en

Enter the preset tare value (clothes weight)

Turn the power on, and check that the "**PT**" mark is displayed. Enter the preset tare value (clothes weight) The tare value range is 0.0 to 10.0kg



Enter ID number

If the ID number function is set to OFF, the scale switches directly to "Measure body weight" without requesting an ID number.

If the ID number is set to ON, ID number will be increased automatically.

To change ID number manually, press (and enter the preferred ID number. The ID number range: 0 to 99999999999999999

ID number setting \rightarrow See P.13 setting 7



Measure body weight

Step onto the platform with bare feet, after **"StEP on**" flashes. **"NET**" is displayed when you have entered a tare value (clothes weight).

The "Stabilised" icon (\mathbf{O}) appears when the load is stable.



Note

Note

When the One step flow is selected, enter personal information first.

 \rightarrow See P.13 Setting 8

If the scale does not detect a load, press (PT) to switch to "Input tare value". If the scale detects the load, press (PT) to display the entered tare value.


4


Select body type **Standard** Standard

If the body type selection (Athletic mode) is set to OFF, the scale switches directly to "Select gender" without requesting a body type.

The " $\mathbf{\hat{x}}$ " mark is displayed when the Athletic mode is selected.

Athletic mode setting \rightarrow See P.13 Setting 9 Athlete condition \rightarrow See P.30






52)

∃pt €

52 ID O ŝ\$₽₽₽€ EDDE

Taking a Measurement (continued)



The scale starts measuring impedance after you have entered all of the personal information.

Wait until **"StAY**" is displayed, and remain standing while measuring.

The measurement is complete when all "••••• disappear. The scale displays the measurement results after measuring the whole body impedance.

The next measuring starts by pressing CEnter.






Measurement Results

Output Measurement Results (Body Composition Mode)

The measurement results are displayed on the LCD after measurement is completed.

The results are output to the PC immediately after measurement is completed.




Press the key to select the measurement display. The measurement display is switched in the following order by


pressing the 🐼 key.

 \rightarrow "Fat" \rightarrow "Muscle" \rightarrow "Body Water" \rightarrow "Visceral fat rating" \rightarrow "Basal metabolic rate" \rightarrow "BMI"—

Body Fat (Applicable age: 5 to 99)



• Muscle (Applicable age: 5 to 99)




*Muscle mass level compared to the general population.


en

Taking a Measurement (continued)


Measurement Results



Sisceral fat rating (Applicable age: 18 to 99)




Basal metabolic rate (Applicable age: 18 to 99)



*Basal metabolic rate level compared to the general population. Note BMR kJ unit display ON/OFF setting \rightarrow See P.13 setting 23

Body Mass Index (BMI) (Applicable age: 5 to 99)



How to Use

How to Use

Scale Mode

The "**T**" icon is displayed when the scale mode is selected.

Enter the ID number

If the ID number function is set to OFF, the scale starts measuring weight immediately. If the ID number is set to ON, ID number will be increased automatically. To change ID number manually, press (and enter the

To change ID number manually, press (and enter the preferred ID number.

The ID number range is from 0 to 9999999999999999.

Press Press to enter tare value (clothes weight). The tare value range is 0.0 to 10.0kg.

Note ID number setting \rightarrow See P.13 setting 7

Measure body weight

Step onto the platform, after "**StEP on**" flashes.

"**NET**" is displayed when you have entered a tare value (clothes weight).

The "Stabilized" icon (**O**) appears when the load is stable. The "Stabilized" icon (**O**) disappears when the load is unstable.


When the load is stable, the measurement results are output via the USB port and stored on an SD card.



Various Criteria

- What is body fat percentage? (Applicable age 5 to 99)

Body fat percentage is the amount of body fat as a proportion of your body weight. Reducing excess levels of body fat has shown to reduce the risk of certain conditions such as high blood pressure, heart disease, diabetes and cancer. The chart below shows the healthy ranges for body fat.



Copyright (C) 2004 TANITA Corporation. All Rights Reserved.

Healthy Range Indicator

Your Body Composition Analyzer automatically compares your body fat percentage reading to the Healthy Body Fat Range chart. After your body fat percentage has been calculated, the bar on the left side of the LCD will light up, identifying where you fall within the Body Fat Ranges for your age and gender.

+ 0 -

(+): Overfat and Obese

Overfat; above the healthy range. Increased risk for health problems. Obese; high above the healthy body fat range. Greatly increased risk of obesity-related health problems.

(0): Healthy; within the healthy body fat percentage range for your age/gender.

(-): Underfat; below the healthy body fat range. Increased risk for health problems.

*Note: Athletes may have a lower body fat range depending on their particular sport or activity.

en

- What is total body water percentage? (Applicable age 5 to 99)

Total Body Water Percentage is the total amount of fluid in a person's body expressed as a percentage of their total weight.

Water plays a vital role in many of the body's processes and is found in every cell, tissue and organ. Maintaining a healthy total body water percentage will ensure the body functions efficiently and will reduce the risk of developing associated health problems.

Your body water levels naturally fluctuate throughout the day and night. Your body tends to be dehydrated after a longnight and there are differences in fluid distribution between day and night. Eating large meals, drinking alcohol, menstruation, illness, exercising, and bathing may cause variations in your hydration levels.

Your body water percentage reading should act as a guide and should not be used to specifically determine your absolute recommended total body water percentage. It is important to look for long-term changes in total body water percentage and maintain a consistent, healthy total body water percentage.

Drinking a large quantity of water in one sitting will not instantly change your water level. In fact, it will increase your body fat reading due to the additional weight gain. Please monitor all readings over time to track the relative change.

Every individual varies but as a guide the average total body water percentage ranges for a healthy adult are:

Female: 45 to 60%Male: 50 to 65%Source: Based on Tanita's Internal Research

Note: The total body water percentage will tend to decrease as the percentage of body fat increases. A person with a high percentage of body fat may fall below the average body water percentage. As you lose body fat the total body water percentage should gradually move towards the typical range given above.

- What is visceral fat rating? (Applicable age 18 to 99)

This feature indicates the rating of visceral fat in your body.

Visceral fat is the fat that is in the internal abdominal cavity, surrounding the vital organs in the trunk (abdominal) area. Research shows that even if your weight and body fat remains constant, as you get older the distribution of fat changes and is more likely to shift to the trunk area especially post menopause. Ensuring you, have healthy levels of visceral fat my reduce the risk of certain diseases such as heart disease, high blood pressure, and the onset of type 2 diabetes.

The Tanita Body Composition Analyzer will provide you with a visceral fat rating from 1 to 59.

Rating from 1 to 12

Indicates you have a healthy level of visceral fat. Continue monitoring your rating to ensure that it stays within the healthy range.

Rating from 13 to 59

Indicates you have an excess level of visceral fat. Consider making changes in your lifestyle possibly through diet changes or increasing exercise.

- Source: 1) Tanita Institute Contract Study. Algorithm Development for Estimating Visceral Fat Rating. SB Heymsfield MD. Columbia University College of Physicians and Surgeons 2004.
 - 2) Wang, Z., et al. Japanese-American Differences in Visceral Adiposity and a Simplified Estimation Method for Visceral Adipose Tissue. North American Association for the Study of Obesity. Annual Meeting. Abstract 518-P. 2004

Note:

- Even if you have a low body fat rate, you may have a high visceral fat level.
- •For medical diagnosis, consult a physician.

Various Criteria (continued)

- What is basal metabolic rate (BMR)? (Applicable age 18 to 99)

What is BMR?

Your Basal Metabolic Rate(BMR) is the minimum level of energy your body needs when at rest to function effectively including your respiratory and circulatory organs, neural system, liver, kidneys, and other organs. You burn calories when sleeping.

About 70% of calories consumed every day are used for your basal metabolism. In addition, energy is used when doing any kind of activity however; the more vigorous the activity is the more calories are burned. This is because skeletal muscle (which accounts for approximately 40% of your body weight) acts as your metabolic engine and uses a large amount of energy. Your basal metabolism is greatly affected by the quantity of muscles you have, therefor increasing your muscle mass will help increase your basal metabolism.

By studying healthy individuals, scientists have found that as people age, their metabolic rate changes. Basal metabolism rises as a child matures. After a peak at the age of 16 or 17, it typically starts to decrease gradually.

Having a higher basal metabolism will increase the number of calories used and help to decrease the amount of body fat. A low basal metabolic rate will make it harder to lose body fat and overall weight.

How does a Tanita body composition analyzer caluclate BMR?

The basic way of calculating Basal Metabolic Rate BMR is a standard equation using weight and age. Tanita has conducted in-depth research into the relationship of BMR and body composition giving a much more accurate and personalized reading for the user based on the impedance measurement. This method has been medically validated using indirect calorimetry (measuring the breath composition).*

* Reliability on equation for Basal Metabolic Rate: At 2002 Nutrition Week: A Scientific and Clinical Forum and Exposition Title: International Comparison: Resting Energy Expenditure Prediction Models: The American Journal of Clinical Nutrition

- What is metaboric age? (Applicable age 18 to 99)

This feature calculates your BMR and indicates the average age associated with that type of metabolism.

If your BMR Age is higher than your actual age, it is an indication that you need to improve your metabolic rate.

Increased exercise will build healthy muscle tissue, which will improve your metabolic age.

You will obtain a reading between 12 and 90. Under 12 will be displayed as "12" and over 90 displayed as "90".

en

- What is muscle mass? (Applicable age 5 to 99)

This feature indicates the weight of muscle in your body.

The muscle mass displayed includes the skeletal muscles, smooth muscles (such as cardiac and digestive muscles) and the water contained in these muscles.

Muscles play an important role as they act as an engine in consuming energy. As your muscle mass increase, your energy consumption increases helping you reduce excess body fat levels and lose weight in a healthy way.


- What is physique rating? (Applicable age 18 to 99)

This feature assesses your physique according to the ratio of body fat ad muscle mass in your body.

As you become more active and reduce the amount of body fat, your physique rating will also change accordingly. Even though your weight may not change, your muscle mass and body fat levels may be changing making you healthier and at lower risk of certain diseases.

Each person should set their own goal of which physique they would like and follow a diet and fitness program to meet that goal.

Result	Physique Rating	Explanation		
1	Hidden obese	Small Frame Obese		
		This person seems to have a healthy body type based on physical appearance; however, they have a high body fat % with low muscle mass level.		
2	Ohaaa	Medium Frame Obese		
2	Obese	This person has a high body fat percentage, with a moderate muscle mass level.		
3	Calially, built	Large Frame Obese		
3	Solidly-built	This person has both a high body fat % and a high muscle mass.		
4		Low Muscle & Average Body Fat%		
4	Under exercised	This person has an average body fat % and a less than average muscle mass level		
5	Chandaud	Ave. Muscle & Ave. Body Fat %		
5 Standard This person has average levels		This person has average levels of both body fat and muscle mass.		
6	Chanderd Museuler	High Muscle & Ave. Body Fat % (Athlete)		
0	Standard Muscular	This person has an average body fat % and higher than normal muscle mass level.		
7	This	Low Muscle & Low Fat		
	Thin	This person has both a lower than normal body fat % and muscle mass level.		
8	Thin and muoaular	Thin and muscular (Athlete)		
0	Thin and muscular	This person has lower than normal body fat % while having adequate muscle mass.		
9	Von Mussular	Very Muscular (Athlete)		
9	Very Muscular	This person has lower than normal body fat % while having above average muscle mass.		



Source : Data from Columbia University (New York) & Tanita Institute (Tokyo)

Represents muscle

Represents fat

Various Criteria (continued)

- What is bone mass? (Applicable age 18 to 99)

This feature indicates the amount of bone (bone mineral level, calcium or other minerals) in the body. Research has shown that exercise and the development of muscle tissue are related to stronger, healthier bones. While bone structure is unlikely to make noticeable changes in a short period, it is important that you develop and maintain healthy bones by having a balanced diet and plenty of exercise. People worried about bone disease should consult their physician. People who suffer from osteoporosis or low bone densities due to advanced age, young age, pregnancy,hormonal treatment or other causes, may not get accurate estimations of their bone mass.

Below is the result of estimated bone masses of persons aged 20 to 40, who are said to have the largest amounts of bone masses, by weight. (Source: Tanita Body Weight Science Institute)

Please use the below charts as a guide to compare your bone mass reading.

Weight (kg)			
Less than 50 kg	50 to 75 kg	75 kg and up	
1.95 kg	2.40 kg	2.95 kg	

Men: Average of estimated bone mass

Weight (kg)			
Less than 65 kg	65 to 95 kg	95 kg and up	
2.66 kg	3.29 kg	3.69 kg	

Note: Persons described below may obtain varying readings and should take the values given for reference purposes only.

- Elderly persons - Women during or after menopause

- People receiving hormone therapy

"Estimated bone mass" is a value estimated statistically based on its correlation with the fat-free mass (tissues other than the fat). "Estimated bone mass" does not give a direct judgment on the hardness or strength of the bones or the risks of bone fractures. If you have concerns over your bones, you are recommended to consult a specialist physician.

en

Output and Storage of Measurement Results

Data Output

Outputting measurement results via the USB or RS

The results are output to the PC immediately after measurement is completed.

Data is output in CSV format.

- USB connector (Type B 4 pin female) and RS-232C are located on the back of the control box.
- Please provide your own cable as necessary as none are included.
- USB cable: Type A 4 pin (male) Type B 4 pin (male)
- Please install the necessary driver on your PC. Drivers can be downloaded from: http://www.tanita.eu
- RS-232C and USB are mutually exclusive.

Data Storage

Data storage of measurement results

The results are saved to the SD card immediately after measurement is completed.

The *sicon* is displayed when a valid SD card is inserted.

A new file is created on the SD card for each day.

The file is created using the measurement date and time as the file name, as shown below. "YYYYMMDD" (year, month and date)

If "error 12" is shown in the display, this indicates that there is not enough free space left on the SD card.

You can store approximately 10,000 measurement results (weight only mode) on a 2GB SD card.

• Do not remove the SD card when it is storing or reading data.

• Do not turn off the main power when the SD card is storing or reading data.

Output and Storage of Measurement Results (continued)

Printing Data

	1	,
Number	Items	Default
45	Fat Mass	1.on
46	Fat Free Mass	1.on
47	Muscle Mass	1.on
48	Total Body Water Mass	1.on
49	Bone Mass	1.on
50	Basal Metaboric Rate (BMR)	1.on
51	Metaboric Age	0.off
52	Visceral Fat Rating	1.on
54	BMI	1.on
56	Ideal Body Weight	0.off
57	Degree of Obesity	0.off
58	Desirable Range Fat % & Fat Mass	1.on
59	Total Body Water %	1.on
60	Graph Fat %	1.on
61	Graph BMI	1.on
62	Graph Visceral Fat Rating	1.on
63	Graph Muscle Mass	1.on
64	Graph BMR	1.on
66	Physiqe Rating	1.on
67	Bioelectrical data	1.on
68	TANITA Logo	1.on

Note 0: off, 1: on

Printing Measurement Results

The results are printed from the printer immediately after measurement is completed. The number of sheets that are printed is set in $\widehat{}_{\text{Setting}}$.

Lists of Contents of the Print Item Preset

Drint item	Body composition analyzer						
Print item		Full Short			Scale		
Body Type	Standard	Athletic	Child	Standard	Athletic	Child	
TANITA LOGO	1	1	1	1	1	1	1
Category Name	1	1	1	1	1	\checkmark	1
Model Number	1	1	1	1	1	\checkmark	1
Date and Time	1	\checkmark	1	1	1	\checkmark	1
ID No	*1	*1	*1	*1	*1	*1	*1
Body Type	1	1		1	1		
Gender	1	1	1	1	1	1	
Age	1	1	1	1	1	1	
Height	1	1	1	1	1	1	
Clothes Weight	1	1	1	1	1	1	1
Weight	1	1	1	1	1	1	1
Fat %	1	1	1	1	1	1	
Fat Mass	1	1	1				
Fat Free Mass	1	1	1				
Muscle Mass	1	1	1				
Total Body Water Mass	1	1	1				
Total Body Water %	1	1	1				
Bone Mass	1	1					
Basal Metabolic Rate	1	1					
Metabolic Age	1	1					
Visceral Fat Rating	1	1					
BMI	1	1	1	1	1	1	
Ideal Body Weight	1						
Degree of Obesity	1						
Desirable Range	1	1	1				
Target Fat %	*1	*1	*1	*1	*1	*1	
Indicator Fat %	1	1	1				
Indicator BMI	✓ ✓						
Indicator Visceral Fat Rating	1	1					
Indicator Muscle Mass		1					
Indicator BMR	· ·						
Physique Rating	✓ ✓						
Bioelectrical Data	✓ ✓		1	1	1		

See P.28 for an example of preset print.

*1: These items are not default.

How to Use

In the Case to Select the Print Item Preset "Body Composition Analyzer - full - Standard"

		• When it is set with an ID, it is printed
Category name	BODY COMPOSITION ANALYZER	out. (The default is without an ID.)
	DC-360	
Weight	26/JAN/2015 20:59	Fat %
• Measured weight.		• Fat % is amount of body fat as a
0	ID No. 0000001234567890	proportion of body weight.
Fat mass	GENDER STANDARD	proportion of body weight.
• Total weight of fat mass in the body.	AGE 35 HEIGHT 180 cm	
	CLOTHES WEIGHT 1.5kg	⊢ FFM
Marcala		• Fat Free Mass is comprised of muscle,
Muscle mass	RESULT WEIGHT 83.0kg	bone, tissue, water, and all other fat
Bone-free lean tissue mass (LTM)	WEIGHT 83.0kg FAT % 25.9 % FAT MASS 21.5kg FFM 61.5kg MUSCLE MASS 54.9 %	free mass in the body.
	1 1100000 11000 100.4691	
TBW %	TBW 48.4kg TBW % 58.3 %	
	BONE MASS 3.1kg BMR 7598 kJ	
BMR*	METABOLIC AGE 50	• Total Body Water is the amount of
• Basal Metabolic Rate represents the	VISCERAL FAT RATING 8	water retained in the body. TBW is
total energy expended by the body to	BMI 25.6 IDEAL BODY WEIGHT	said to comprise between 50% to 70%
maintain normal functions at rest such	DEGREE OF OBESITY	of total body weight. Generally, men
	16.4 %	tend to have higher water weight than
as respiration and circulation.	DESIRABLE RANGE	women due to a greater amount of
	FAT % 8.0 - 19.9 % FAT MASS	muscle.
Visceral fat rating*	5.3 - 15.3kg	musee.
Visceral fat rating feature indicates the	TARGET	
rating of visceral fat.	TARGET BF% is: 15 %	Bone mass*
	Predicted weight: 72.4kg	Bone mineral amount included in the
Ideal body weight*	Predicted fat mass: 10.9kg	entire bone.
• Ideal body weight is a value for which	FAT TOĂLOSE: 10.6kg	
the BMI is 22.	Consult your physician	└── Metabolic age*
	before beginning any weight management pro-	Metabolic age is evaluated young
Degree of obesity*	gram.Tanita is not re- sponsible for deter-	when a muscular amount is larger, and
• Calculated as (weight – Ideal body	mining your targetBF%.	BMR is higher.
weight) / Ideal body weight × 100.	INDICATOR	Divite is higher.
(in english) / Talear 2004) (in english 2004)	*FAT %	
	- ; U ; + ; ++	└── BMI
		 Calculated with "weight (kg) /
	*VISCERAL FAT RATING	height(m)²″
	13	
	*MUSCLE MASS	The desirable range is for the Standard
		mode. In the case of the Athletic mode,
	*BMR	the standard value is just a reference. And
	- 0 +	for those who are 17 years old or younger,
	*PHYSIQUE RATING	only the body fat % is displayed as the
Bioelectrical data	OBESE	standard value. The muscle mass, total
• The Resistance Reactance table		
indicates measurements for the	*BIOELECTRICAL DATA 6.25kHz 50kHz	body water and the estimated bone mass
impedance flow at each of the two	*BIOELECTRICAL DATA 6.25kHz 50kHz R 433.5 394.3 X -19.3 -29.0	for those who are 17 years old or younger
dual frequency singals.		are for reference.
1, 0		

*18 to 99 yaers only



Please consult your doctor before you start a body weight management program. Tanita is not responsible for the target body fat ratio.

en

en

Reading Stored Measurement Result Data

Press the setting key while the display is on, and select the setting 80.

Make sure the SD card is inserted.


Enter the measurement date (YYYYMMDD) using the keypad, then press the Enter key and "oPEn" lights.

When there is no data matching with the entered date, "F-nonE" is displayed.

2 When a file is present, the ID and measurement date and time of the data saved at the beginning of the file are alternately displayed.

- (1) Press the 🚱 key, and the ID and measurement date and time of the data saved below are alternately displayed.
- (2) Press the Enter key, and Body weight, Pt (Clothes weight) and Body Fat % are displayed.

*Press the CE key to return to one higher level.









Output and Storage of Measurement Results (continued)

How to Use

General Instructions for Body Composition Measurement

Athletic Mode

- Recommended for those who are 18 years or older and meet the following conditions.
- People who carry out 12 hours or more of cardiovascular exercise a week.
- People who belong to a sport team or a sport organization with the aim of participation in competition, etc.
- People who are professional athletes.

Target Body Fat

• A target body fat % should be set by a professional only. Tanita is not responsible for setting the appropriate target body fat % for specific individuals.

Attention

- Posture when measuring
- Stand with both feet parallel on the electrodes.
- Stand without bending knees.
- The age input range is 5 to 99 years old. Input age 99 for those who are 100 years or older.


Note

- •Inaccurate results may be reported after excessive food/fluid intake, or after periods of intense exercise.
- If clothes weight is input, clothes weight is subtracted from the weight measurements.

30

Troubleshooting

Please check the following before requesting repair.



If Necessary

Technical Notes

Body composition measurement by the BIA method.

Introduction

This equipment provides estimated values for each measured value of body fat percentage, fat mass, fatfree mass, muscle mass and bone mass by the DXA method, estimated value for the total body water measured value by the dilution method and estimated value for the visceral fat rating by MRI method using the Bioelectrical Impedance Analysis (BIA method).

For measurement, a mode must be selected based on body type.

1) Standard (for 5 to 99 years of age)

2) Athletic (for Athletic persons who exercise considerably more than non-athlete)

Making a distinction by body type in the measurement mode produces more reliable body composition measurements for athletic persons, whose body compositions differ from those of average persons.


- Principles of body composition measurement

BIA is a means of measuring body composition – fat mass, predicted muscle mass, etc. – by measuring bioelectrical impedance in the body. Fat within the body allows almost no electricity to pass through, while electricity passes rather easily through water, much of which is found in muscles. The degree of difficulty with which electricity passes through a substance is known as the electrical resistance, and the percentage of fat and other body constituents can be inferred from measurements of this resistance.

The Tanita Body Composition Analyzer measures body composition using a constant current source with a high frequency current (6.25kHz, 50kHz, 90 μ A). The 4 electrodes are positioned so that electric current is supplied from the electrodes on the tips of the toes of both feet, and voltage is measured on the heel of both feet.

- What is the DXA method?

DXA was originally designed to measure bone mineral content, but in the full-body scan mode the body fat percentage, fat mass, and fat free mass of individual body parts (arms, legs, trunk) can also be measured. The image below shows one example of body composition measurement results obtained by DXA.



Body composition measurement results obtained by DXA

- What is dilution method?

In the dilution method, a labeled substance for a known amount is given and the concentration in equilibrium diffusing evenly is measured to obtain the total amount of the solvent that dilutes the labeled substance.

To measure the total body water (TBW), deuterium oxide (D_2O) is generally used as the labeled substance. Deuterium oxide uses the overall total body water as dilution space so the total body water can be obtained. To obtain the extracellular fluid amount, sodium bromide (NaBr) is used as a labeled substance. Bromine (Br) is said to not enter the inside of cells, and uses extracellular fluid as the dilution space.

en


- What is the visceral fat?

Visceral Adipose Tissue (VAT) has been associated with increased risk of developing lifestyle-related diseases. Accordingly, knowing and periodically checking the estimated VAT accumulation serves as one factor of a number of factors in assessing the prevention of lifestyle related diseases.


Tanita has developed the technology for measuring the VAT accumulation risk through bioelectrical impedance analysis (BIA) in comparison with image analysis applied to magnetic resonance imaging (MRI), in addition to the established technology for measuring the percent of body fat. The VAT accumulation risk is calculated by estimating the VAT area by the BIA method on the basis of MRI image processing. This method has a higher correlation than the estimation of the VAT accumulation risk based on BMI or abdominal circumference (waist circumference), allowing estimation that corresponds more precisely to individuals.

*The VAT area by MRI is calculated by carrying out an image processing of the cross section of the lumber vertebra L4-L5 regions.

(Fig. 1 - Fig. 3: Research results by N. Y. Columbia University and Jikei University Published by the North American Association for the Study of Obesity [NAASO] in 2004.)



<Fig. 3> Relationship between VAT Area by MRI and Estimated VAT Area by Tanita's BIA



Technical Notes (continued)

- Factors giving errors in measurement

In the BIA method, impedance is measured and the body composition is calculated based on the value. It is known that impedance changes by the amount of the total body water that occupies about 60% of weight and the change in its distribution and temperature change. Therefore, for the purpose of research or for daily repeating of measurements, the measurement conditions must be kept constant. Measurement under the changing conditions of temperature and total body water distribution or blood flow volume of extremities due to exercising, taking a bath, etc., affects the measurement result since the electric resistance in the body also changes.

Therefore, it is recommended to measure under the following conditions for stable measurement.

- 1) 3 hours have passed after getting up and normal lifestyle activities are carried out during this period.
 - (Bioelectrical impedance remains high if you remain sitting after getting up or drive a car, etc.)
- 2) 3 hours or more have passed after eating. (For 2 to 3 hours after eating, the impedance has a tendency to decrease.)
- 3) 12 hours or more have passed after vigorous exercise for measurement. (The tendency toward changes in impedance is not stable depending on the type and rigorousness of the exercise.)
- 4) If possible urinate before taking measurement.
- 5) For repeated measurements, measure at the same hour as much as possible. (At the same time of measurement of weight, the measurements can be made more stable by measuring at the same time of the day)


Very stable measured values can be obtained by measuring under the above conditions. And in the development of this equipment, the following 6 items were set as conditions for the regression equation.

- 1) Prohibition of alcohol intake for 12 hours before measurement
- 2) Prohibition of excessive exercise for 12 hours before measurement.
- 3) Prohibition of excessive eating and drinking the day before measurement
- 4) Prohibition of eating and drinking for 3 hours before measurement
- 5) Urination just before measurement
- 6) Avoid measurements during menstruation (for female)

2) Inter-day changes

The diagrams below offer examples of actual measurements made of inter-day changes. A study was done to determine the degree of change in the impedance between the feet during dehydration; the first two days represent a normal daily routine, while in the latter two days a state of dehydration was induced using a sauna. No significant inter-day change was measured in body weight, impedance between the feet, or body fat percentage during the normal daily routine. During the dehydrated state, however, a drop in body weight of 1kg was noted, with the impedance between the feet rising approximately 15 Ω on the first day of dehydration and 30 to 35 Ω on the second day. As a result, body fat percentage was up by around 1% on the first day of dehydration and by 1.5 to 2% on the second day.

As mentioned earlier, impedance increases when body weight is reduced (such as by dehydration), and decreases when body weight is increased through excess consumption of food and drink. The inter-day change in impedance is thus inversely proportional to the change in body weight.



(en)

en

These inter-day changes stem from such causes as:

1) Temporary increases in body weight (total body water) through overeating and overdrinking

2) Dehydration due to heavy sweating during vigorous exercise


3) Dehydration due to alcohol consumption or the use of diuretics

4) Dehydration due to heavy sweating during saunas, etc.

Accordingly, it is recommended that instructions be provided to the subject to help eliminate these causes when accurate measurements are needed.

The Regression Formula for Basal Metabolic Rate (BMR)

The Basal Metabolic Rate (BMR) value is known to be closely related with the Fat Free Mass (FFM). It is also correlated with body weight, but there are issues when it is calculated from the body weight without considering body composition evaluation. This causes a greater error range to occur. In cases where people have the same body weight but different composition, values for obese people that have more body fat are overestimated, whereas those for muscular athletes are underestimated.




<Figure 1> Relationship of BMR from exhalation analysis with weight and FFM

Figure 1 shows that the correlation between BMR and FFM is far stronger than the correlation between BMR and weight.

The estimated regression equation for BMR developed through years of research by Tanita is extremely accurate because it reflects differences in individual body compositions and is calculated from the measured FFM. This estimated regression equation is based on the BMR measured using an exhalation analyzer, and has been checked for statistical validity.

These results were presented at the First Annual Nutrition Week (American College of Nutrition, American Society for Clinical Nutrition, American Society for Parenteral and Enteral Nutrition, North American Association for the Study of Obesity) held in 2002 in San Diego.

NOTE: This model has been calibrated for those between ages of 18 to 84. Those individuals outside of this age range may not be obtain accurate readings.



<Figure 2> Relationship of BMR and calculated REE from Tanita multiple regression analysis model Modified based on data announced at Nutrition Week held in San Diego in 2002)

en

Specifications

Madel Number DC 200			
Model Number		DC-360	
Derver O		AC adapter	
Power Source		Input:100 – 240V	
		Output:12V	
Electric	Current Range	25VA	
	Measurement System	Dual-frequency 4 electrode	
	Measurement Frequency	6.25kHz / 50kHz	
Impedance Measurement	Electrode Materials	Stainless steel	
	Measurement Part	Between both feet	
	Measurement Range	150.0 to 1,000.0 Ω (0.1 Ω increments)	
	Accuracy at First Calibration	±2%	
Weight Measurement	Measurement System	Strain gauge load cell	
	Range	2 to 270kg (including preset tare value)	
	Minimum Graduation	0.1kg	
	Accuracy at First Calibration	±0.2kg	
Display		LCD screen	
Interface		USB 2.0 (Type B connector)	
		RS-232C	
		SD card	
Usage Conditions	Temperature	5 to 35°C	
Range	Relative Humidity	30 to 80% (non-condensing)	
Storage Conditions	Temperature	-10 to 60°C	
Range	Relative Humidity	10 to 90% (non-condensing)	
	Remote Display Version	8.3kg	
Product Weight	Column Mounted Version	11.2kg	
	Platform	395mm x 390mm x 67mm	
Product Size	Height (Column Mounted Version)	1027mm	

Input Items	Clothes Weight	0.0 to 10.0kg (0.1kg increments)	
	ID No.	16 digits	
	Gender	Female / Male	
	Body Type	Standard / Athletic *1	
	Age	5 to 99 years	
	Height	90.0 to 249.9cm (0.1cm increments)	
	Target Body Fat %	4 to 55% (1% increments)	
	ID No.	16 digits	
	Gender	Female / Male	
	Body Type	Standard / Athletic *1	
	Age	5 to 99 years	
	Height	90.0 to 249.9cm (0.1cm increments)	
	Clothes Weight	0.0 to 10.0kg (0.1kg increments)	
	Weight	2.0 to 270.0kg (0.1kg increments)	
	Fat %	3.0 to 75.0% (0.1% increments)	
	Fat Mass	0.1kg increments	
Output Itomo	FFM	0.1kg increments	
Output Items	Muscle Mass	0.1kg increments	
	BMI	0.1 increments	
	Bone Mass *2	0.1kg increments	
	Metabolic Age*2	1 year increments	
	Basal Metabolic Rate *2	1kcal / 1kJ increments	
	Visceral Fat Rating *2	1 to 59 (1 increments)	
	TBW	0.1kg increments	
	TBW %	0.1% increments	
	Physique Rating *2	9 ratings	
	Bioelectrical Data	Resistance / Reactance	

en

*1 Athletic mode can be selected only 18 to 99 years old

*2 18 to 99 years old

The product design and specifications may be changed at any time without prior notice.

This device meets the EMC Directive 2014/30/EU and the RoHS Directive 2011/65/EU.

Disposal

This equipment is an electronic device.
Please dispose of this equipment appropriately , not as general household waste. Be sure to follow the regulations in your area when disposing of this equipment.

<EU Representative> TANITA Europe B.V.

Hoogoorddreef 56-E, 1101 BE Amsterdam, the Netherlands TEL: +31-(0)20-560-2970 FAX: +31-(0)20-560-2988 www.tanita.eu

TANITA Health Equipment H.K. Ltd.

Unit 301-303, Wing On Plaza, 3/F., 62 Mody Road, Tsimshatsui East, Kowloon, Hong Kong TEL: +852-2834-3917 FAX: +852-2838-8667 www.tanita.asia

<Manufacturer> TANITA Corporation

1-14-2 Maeno-cho, Itabashi-ku, Tokyo 174-8630 Japan TEL: +81-(0)3-3968-7048 www.tanita.co.jp

TANITA India Private Limited

A-502, Mittal Commercia, Off. M.V. Road (Andheri Kurla Road), Marol, Andheri-East, Mumbai 400059, Maharashtra, India TEL: +91-771-801-1511 / +91-771-801-1382 FAX: +852-2838-8667 www.tanita.co.in

TANITA Corporation of America, Inc.

2625 South Clearbrook Drive, Arlington Heights, Illinois 60005 U.S.A. TEL: +1-847-640-9241 FAX: +1-847-640-9261 www.tanita.com

TANITA (Shanghai) Trading Co., Ltd.

Room 8005, 877 Huai Hai Zhong Lu, Shanghai, The People's Republic of China TEL: +86-21-6474-6803 FAX: +86-21-6474-7901 www.tanita.com.cn